



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Clear Toughened	
Product Code	4CT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Clear Toughened	
Product Code	5CT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Clear Toughened	
Product Code	6CT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	8 Clear Toughened	
Product Code	8CT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	10 Clear Toughened	
Product Code	10CT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	12 Clear Toughened	
Product Code	12CT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	19 Clear Toughened	
Product Code	19CT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Low Iron Toughened	
Product Code	4LT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Low Iron Toughened	
Product Code	5LT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Low Iron Toughened	
Product Code	6LT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	8 Low Iron Toughened	
Product Code	8LT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	10 Low Iron Toughened	
Product Code	10LT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	12 Low Iron Toughened	
Product Code	12LT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	19 Low Iron Toughened	
Product Code	19LT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Satin Clear Toughened	
Product Code	4CSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Satin Clear Toughened	
Product Code	6CSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	8 Satin Clear Toughened	
Product Code	8CSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	10 Satin Clear Toughened	
Product Code	10CSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	12 Satin Clear Toughened	
Product Code	12CSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Satin Low Iron Toughened	
Product Code	4LSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Satin Low Iron Toughened	
Product Code	6LSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	8 Satin Low Iron Toughened	
Product Code	8LSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	10 Satin Low Iron Toughened	
Product Code	10LSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silcate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	12 Satin Low Iron Toughened	
Product Code	12LSATT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Bronze Satin Toughened	
Product Code	6BSSAT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Bronze Toughened	
Product Code	4BRZT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Bronze Toughened	
Product Code	5BRZT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Bronze Toughened	
Product Code	6BRZT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	8 Bronze Toughened	
Product Code	8BRZT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	10 Bronze Toughened	
Product Code	10BRZT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	12 Bronze Toughened	
Product Code	12BRZT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Grey Toughened	
Product Code	4GRYT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Grey Toughened	
Product Code	5GRYT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Grey Toughened	
Product Code	6GRYT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	8 Grey Toughened	
Product Code	8GRYT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	10 Grey Toughened	
Product Code	10GRYT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	12 Grey Toughened	
Product Code	12GRYT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Green Toughened	
Product Code	4GRNT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Green Toughened	
Product Code	5GRNT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Green Toughened	
Product Code	6GRNT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 K Toughened	
Product Code	4KT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 K Toughened	
Product Code	6LT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Stopsil Toughened	
Product Code	4STOPT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silcate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Minster Toughened	
Product Code	4MINT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silcate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Delta Toughened	
Product Code	4DELT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Chinchilla Toughened	
Product Code	4CHINT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Stippolyte Toughened	
Product Code	4STIPT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silcate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Flemish Toughened	
Product Code	4FLEMT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Optiview Toughened	
Product Code	4ARP1T	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silicate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Optiview Toughened	
Product Code	5ARP1T	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silcate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Mirrorpane Toughened	
Product Code	4MIRPT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silcate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Mirrorpane Toughened	
Product Code	6MIRPT	
Year marking was affixed	17	
Intended Use	Thermally toughened soda lime silcate glass, intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN12150-2 : 2004	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Clear Heat Soak Toughened	
Product Code	4HST	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Clear Heat Soak Toughened	
Product Code	5HST	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Clear Heat Soak Toughened	
Product Code	6HST	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	8 Clear Heat Soak Toughened	
Product Code	8HST	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	10 Clear Heat Soak Toughened	
Product Code	10HST	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	12 Clear Heat Soak Toughened	
Product Code	12HST	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	19 Clear Heat Soak Toughened	
Product Code	19HST	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Bronze Heat Soak Toughened	
Product Code	4BRZT	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Bronze Heat Soak Toughened	
Product Code	5BRZT	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Bronze Heat Soak Toughened	
Product Code	6BRZT	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	8 Bronze Heat Soak Toughened	
Product Code	8BRZT	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	10 Bronze Heat Soak Toughened	
Product Code	10BRZT	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	12 Bronze Heat Soak Toughened	
Product Code	12BRZT	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Grey Heat Soak Toughened	
Product Code	4GRYTHS	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Grey Heat Soak Toughened	
Product Code	5GRYTHS	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Grey Heat Soak Toughened	
Product Code	6GRYTHS	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	8 Grey Heat Soak Toughened	
Product Code	8GRYTHS	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	10 Grey Heat Soak Toughened	
Product Code	10GRYTHS	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	12 Grey Heat Soak Toughened	
Product Code	12GRYTHS	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	4 Green Heat Soak Toughened	
Product Code	4GRNTHS	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	5 Green Heat Soak Toughened	
Product Code	5GRNTHS	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	6 Green Heat Soak Toughened	
Product Code	6GRNTHS	
Year marking was affixed	17	
Intended Use	Heat soaked thermally toughened soda lime silicate glass, intended to be used in buildings and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14179-2 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(C)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed: 

Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	9.5 Toughened Laminated Toughened	
Product Code	9.5TLAM	
Year marking was affixed	17	
Intended Use	Toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	11.5 Toughened Laminated Toughened	
Product Code	11.5TLAM	
Year marking was affixed	17	
Intended Use	Toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	13.5 Toughened Laminated Toughened	
Product Code	13.5TLAM	
Year marking was affixed	17	
Intended Use	Toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	17.5 Toughened Laminated Toughened	
Product Code	17.5TLAM	
Year marking was affixed	17	
Intended Use	Toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	21.5 Toughened Laminated Toughened	
Product Code	21.5TLAM	
Year marking was affixed	17	
Intended Use	Toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	9.5 Toughened Laminated HS Heat Soak Toughened	
Product Code	9.5TLAMHS	
Year marking was affixed	17	
Intended Use	Heat soaked toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	11.5 Toughened Laminated HS Heat Soak Toughened	
Product Code	11.5TLAMHS	
Year marking was affixed	17	
Intended Use	Heat soaked toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	13.5 Toughened Laminated HS Heat Soak Toughened	
Product Code	13.5TLAMHS	
Year marking was affixed	17	
Intended Use	Heat soaked toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	17.5 Toughened Laminated HS Heat Soak Toughened	
Product Code	17.5TLAMHS	
Year marking was affixed	17	
Intended Use	Heat soaked toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024



Declaration of Performance

Manufacturer	MiGlass Limited 51 Downing Street Smethwick West Midlands B66 2PP	
Product Type	21.5 Toughened Laminated HS Heat Soak Toughened	
Product Code	21.5TLAMHS	
Year marking was affixed	17	
Intended Use	Heat soaked toughened laminated safety glass intended to be used in building and construction works	
System of Attestation of Conformity	System 3	
Applicable Standard	EN 14449 : 2005	
Third Party Approval License No.	KM 658201	
Certification Body and ID number	BSI	0086

Characteristics	Performance
Resistance to fire	NPD
Reaction to fire	NPD
External fire performance	NPD
Bullet resistance	NPD
Explosion resistance	NPD
Burglar resistance	NPD
Pendulum body impact resistance	1(B)1
Resistance against sudden temperature change and temperature differentials	NPD
Wind, snow, permanent and imposed load resistance	NPD
Direct airbourne sound insulation	NPD
Thermal properties	NPD
Light transmission and reflection	NPD
Solar energy characteristics	NPD
Normal Emissivity	NPD

It is the responsibility of the user(s) of this information to ensure the use of the glass product complies with all relevant laws, regulations, standards and is fit for purpose.

This declaration is issued under the sole responsibility of the manufacturer.

Signed:



Position: Managing Director

Date: 27/11/2024